



		Tires		Clutch settings		Front shocks		Engine		
Date/Track	1.12.2014 NEXT	Front shore	left 2635/42 / right 2635/42	Shoe	T2705	Piston	1.1 x 3	Type	OS 12TG	
Driver	Tsuguo Kitade	Rear shore	left 40 / right 40	Bell clearance (mm)	0.5	Oil	600	Plug/Fuel	Plug P3 / Fuel COSMO	
Temp. °C.	air / track	Front φ	left 60 / right 60	Spring	H0764 GOLD	Spring	N2104 ｼﾞﾙ-	Pipe/Manifold	Pipe RE1301 / Manifold	
Track layout/traction	technical <input type="radio"/> low <input type="radio"/> mixed <input checked="" type="radio"/> medium <input type="radio"/> fast <input type="radio"/> high <input checked="" type="radio"/>	Differential		Gearing		Rear shocks		Gear ratio chart		
		Front diff. oil cst.	# 80,000	1st gear	14 / 54	Piston	1.1 x 3	Spur Pinion	1st	2nd
		Rear diff. oil cst.	#50,000	2n gear	19 / 47	Oil	600	1st	14 7,614 7,761 7,907	15 7,107 7,243 7,38
						Spring	N2105 ｼﾞﾙ-	2nd	19 5,071 5,179 5,278	20 4,818 4,92 5,023
								21	4,588 4,686 4,783	

